



HPS C15 A6 HT400 LH

Serial-No.: 1911150

Year of manufacture: 2019

Hochdruckpumpenservice GmbH
Schmolkamp 4B
D-29358 Eicklingen
Germany

Tel: +49 (0) 5144-1869
Fax: +49 (0) 5144-56605
Email: info@hps-celle.de
Web: www.hps-celle.de

1. Technical data

1.1 Dimensions of the pump container

Soundproof container with the following dimensions:

-Length:	6050 mm
-Width:	2440 mm
-Height:	2590 mm
-Weight:	12500 kg

1.2 Engine performance data

Caterpillar: C-15 ATAAC
DIRECTIVE Stufe IIIA und U.S. EPA & CARB Tier III certified
-Power: 588 BHP at 2100 rpm
Operating hours: 2020 h

1.3 Performance data gearbox

Allison Getriebe Serie CLBT 6061-4 (refurbished)

Operating hours:	2020 h
Gear ratio:	1. Gear = 4,00:1
	2. Gear = 2,68:1
	3. Gear = 2,01:1
	4. Gear = 1,35:1
	5. Gear = 1,00:1

1.4 Performance data high pressure pump

High pressure pump: HT400 LH (refurbished)
Operating hours: 1400 h
Drive flange: Spicer series 1800
Input rotation direction: clockwise looking at flange
Input speed: max. 280 rpm
Gear ratio: 8,6:1
Oil lubrication: Gear pump driven via PTO gearbox
Oil filter: Replaceable filter elements and magnetic filter
(HPS-oil-filter-system)

Oil quantity: 21,1 gal
Oil type: Mobil SHC-632
Oil pressure: 80-100 psi
Weight dry: 5510 lbs



1.5 Performance data Fluid-End

Size:	3 3/8" – 6"
Plunger type:	Simple working, surface treated
Valve type:	Double guided valves made of special steel
High pressure seal:	Special packing
High pressure connection:	3" or 2" Weco 1502
Plunger oil system:	Plunger circulation lubrication with compensation
Spacer design:	L4
Pressure max.:	15000 psi (Continuous run)
Flow rate max:	710 gpm

Contact Rental: HPS Rental GmbH
Schmolkamp 4B
D-29358 Eicklingen
info@hps-rental.de
+49 5144 - 4933752